

PPG Coatings Nederland BV
Oceanenweg 2
NL 1047 BB Amsterdam
NETHERLANDS

Eurofins Product Testing Denmark A/S
Smedeskovvej 38
8464 Galten
Denmark

DK-CustomerSupport@cpt.eurofinseu.com
www.eurofins.com

TEST REPORT

VOC/SVOC Content

24 August 2026

1 Sample Information

Sample name	Sigma S2U Nova Primer
Batch no.	Lab sample / EM001
Stated production date	22/04/2026
Sample reception	27/04/2026

2 Brief Evaluation of the Results

Regulation or protocol	Conclusion	Version of regulation or protocol
Decopaint	Pass	Directive 2004/42/CE
EU Ecolabel for paints and varnishes	Pass	Commission Decision 2025/2607 of 17 December 2025 establishing the EU Ecolabel criteria for decorative paints, varnishes, and related products, performance coatings and related products, and water-based aerosol spray paints

Full details based on the testing and direct comparison with limit values are available in the following pages
Regarding pass/fail decision rule please see appendix



Janne Rothmann Norup
Analytical Service Manager



Rasmus Verdier
Analytical Service Manager

3 Applied Test Methods

3.1 General Test References

Regulation, protocol or standard	Scope	Version
Decopaint	Paints and varnishes	Directive 2004/42/CE
EU Ecolabel for paints and varnishes	Paints and varnishes	Commission decision (EU) 2025/2607

3.2 Specific Laboratory Sampling and Analyses

Test	Regulation, protocol or standard	Version	Internal SOP	Limit of detection [mg/kg]	Uncertainty U _m %
VOC/SVOC	ISO 11890-2	2020	71 M 546002	50	20
Density *	Internal method	-	71 M 543130	-	10

4 Results

4.1 Results Used in Calculation

	Remarks on the test results	Results	Unit
Density *	Tested by the lab	1.30	g/mL

4.2 Total VOC Content

	CAS No.	Retention time	ID-Cat	Results	Unit
N,N-Dimethyl-2-aminoethanol *	108-01-0	5.65	Q1	1.3	g/L
Unidentified substances *	-	6.99-20.13	Q2	0.64	g/L
2-Ethyl-1-hexanol *	104-76-7	12.83	Q1	0.20	g/L
Dipropylenglykol- mono-n-butylether (two isomers) *	29911-28-2	18.2	Q1	22	g/L
VOC content				24	g/L

4.3 Total SVOC Content

	CAS No.	Retention time	ID-Cat	Results	Unit
2,4,7,9-Tetramethyl-5-decin-4,7-diol *	126-86-3	20.76	Q2	0.9	g/L
Unidentified substances *	-	22.99-28.68	Q2	1.2	g/L
SVOC content				2.1	g/L

4.4 Comparison with Limit Values of VOC Content

Parameters	Results	Product type	Regulation or protocol	VOC limit
	[g/L]			[g/L]
VOC content	24	Interior/exterior trim and cladding paints for wood and metal, WB	Decopaint	130
			EU Ecolabel	60
SVOC content	2.1		EU Ecolabel	40

5 Appendices

5.1 How to Understand the Results

5.1.1 Acronyms Used in the Report

<	Means less than
>	Means bigger than
*	Not a part of our accreditation
1	Analysed by another Eurofins laboratory

5.1.2 Explanation of ID Category

Categories of Identity:

Q1: Identified by comparison with a mass spectrum obtained from library and supported by other information and quantified through specific calibration.

Q2: Identified by comparison with a mass spectrum obtained from library and supported by other information. Quantified as diethyladipate.

5.2 Description of VOC/SVOC Content Test

5.2.1 Testing of VOC/SVOC (ISO 11890-2)

Volatile Organic Compounds (VOC) include all organic compounds with an initial boiling point less than or equal to 250 °C measured at standard pressure of 101.3 kPa.

Semi-Volatile Organic Compounds (SVOC) include all organic compounds with an initial boiling point greater than 250 °C and less than 370 °C measured at standard pressure of 101.3 kPa.

The determination is performed in conformity with ISO 11890-2 and the commission decision 2014/312/EU of 28 May 2014 establishing the ecological criteria for the award of the EU Ecolabel for indoor and outdoor paints and varnishes, with its most recent amendments and its most recent User Manual.

Analyses are performed with a slightly polar gas chromatographic column (HP-5). Mass spectrometric detection is used for identification and flame ionization detector is used for quantification. Identified compounds are quantified with their authentic response factors, or with their relative response factors using 1,2-diethoxyethane as internal standard. Remaining unknown peaks are quantified in diethyl adipate equivalents.

5.2.2 Testing of Density

The density was calculated using gravimetric and volumetric determination. The result is the average of three determinations.

5.3 Uncertainty of the Test Method

Um(%): The expanded uncertainty Um is equal to 2 x RSD%.

5.4 Decision Rules

Eurofins Product Testing A/S, declare statement of conformity based on the "Binary Statement for Simple Acceptance Rule" described in ILAC's "Guidelines on decision Rules and Statements of Conformity" ILAC-G8:09/2019.

This means that results above the detection limit are always reported with two significant digits. Results are

The analysis are carried out on the sample(s) as received and the result(s) are only valid for the tested sample(s).

This report may only be copied or reprinted in its entirety.

evaluated with the same number of significant digits as the corresponding limit values, and conformity is based on results being less than or equal to limit values.

For limit values with more than two significant digits, the third digit will be used to confirm whether a result is below or equal to the limit value. It will always be indicated in the evaluation table if this expanded evaluation is performed.

For further information, please visit www.eurofins.dk/product-testing/om-os/beslutningsregler/

5.5 Version History

Report date	Report number	Modification
24/08/2026	392-2026-00211502_XG_EN_rev1	Revision of evaluated product type from "Primer, WB" to "Interior/exterior trim and cladding paints for wood and metal, WB". Correction of conclusion for EU Ecolabel from fail to pass. This version is considered valid.
06/07/2026	392-2026-00211502_XG_EN	This version is no longer valid.