

DESCRIPTION

Johnstone's Trade Performance Coatings Quick Drying Steel & Cladding Topcoat has been specially formulated to provide anticorrosive protection on suitably primed, new, pre-treated, weathered, or previously painted metal and plastisol cladding. With its water-based technology it provides a quick drying, sprayable solution in a satin finish to transform cladding and other metal structures to offer up to 8 years protection.

RECOMMENDED USES



Plastisol cladding, suitably prepared steel and other metal surfaces.

COLOUR RANGE

Available in 10,000 colours via the Johnstone's Tinting System.

FINISH

Satin.

VOLUME SOLID

45%

COVERAGE



Johnstone's Trade Performance Coatings Quick Drying Steel & Cladding Topcoat will cover approximately 7-11 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

Wet: 90-130µm, dry: 40-60µm.

DRYING TIME



Touch dry in 1 hour. Recoatable after 8 hours. High humidity and low temperatures will prolong drying times.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. PROTECT FROM FROST.

THINNER

Cleaner: Clean Water.

VOC CONTENT

EU limit value for this product (Cat A/d): 130g/l (2010). This product contains max 110g/l VOC.



KEY PROPERTIES

- Up to 8 Years Protection
- Quick Drying
- Excellent Adhesion
- Satin Finish

PREPARATION

CLADDING: All surfaces to be painted should be clean, dry and free from loose and flaking material, cleaned using Johnstone's Trade Cleaner and Degreaser and allowed to dry. All bare areas of steel/aluminium must be suitably prepared and spot primed using Johnstone's Trade Advanced Multi-Surface Primer.

STEEL: Prepare surface and prime using Johnstone's Trade Advanced Multi-Surface Primer. If overcoating an existing paint ensure the surface is clean and dry. Special precautions should be taken during surface preparation of pre-1960 paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com

APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir thoroughly before use. Suitable for application by brush, roller or spray. Do not apply in temperatures below 8°C or externally when rain is imminent. If more than one tin of a colour is to be used in the same area, intermix before use.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZE

5 Litre