



CFX 1972 High Build Additive

ONECHOICE® Commercial CFX1972 is designed for use in various Refinish Light Industrial (LIC) and Commercial Transport (CT) topcoat qualities. It can be used in solid and metallic colors and the amount recommended must be strictly observed. Use of quantities greater than what is recommended may result in poor durability, poor chemical and water resistance, potential delamination, solvent pop (due to excessive film), poor flow and softer paint films.

CFX1972 is intended to improve “hang” or vertical stability in approved topcoats where needed on sharp edges or rivets.

CFX1972 is approved only in the following products

PPG VERSOLON™ AUE-280, AUE-300, AUE-360, DELFLEET ESSENTIAL® and DELFLEET® EVOLUTION FDGU and FDGH

Mix Ratio

Compatible Product	CFX1972	Compatible Product	CFX1972
1 gallon RTS color (128 ounces)	6 ounces	5 gallons RTS color (640 ounces)	30 ounces
1-gallon RTS Package color (128 ounces)	8 ounces	5 gallons RTS Package color (640 ounces)	40 ounces

Application

Once CFX1972 is added to the topcoat, agitation for five minutes on a mechanical agitator is required to fully incorporate the additive into the color. Improper agitation of the incorporated additive will result in a “chunky” or “lumpy” appearance when applied. **Hand agitation is insufficient and NOT recommended.**

Technical Properties*

Percent Solids (wt)	41.25 %	VOC Regulatory (less water less exempt) (lbs/gal)*	4.93 lbs/gal
Percent Solids (vol)	33.65 %	Density (g/L)	1005.8 g/l
HAPs	0.00 lbs/gal	Density (lbs/gal)	8.39 lbs/gal
Photochemically Reactive	Yes	Volatiles wt. %	58.75 %
Flash Point	25 °F	Water wt. %	0 %
VOC Actual (g/L)	591.0 g/l	Exempt wt. %	0 %
VOC Actual (lbs/gal)	4.93 lbs/gal	Water vol. %	0 %
VOC Regulatory (less water less exempt) (g/L)	591.0 g/l	Exempt vol. %	0 %

* Use of CFX1972 may result in VOC being beyond the published values on individual product data sheets



Improper handling & application of products could impact product safety and performance. Read the product label and SDS before use.

EMERGENCY MEDICAL OR SPILL CONTROL INFORMATION (412) 434-4515;
IN CANADA (514) 645-1320

Materials described are designed for application by professional, trained personnel using proper equipment and are not intended for sale to the public. Products mentioned may be hazardous and should only be used according to directions, while observing precautions and warning statements listed on label. Statements and methods described are based upon the best information and practices known to PPG Industries Inc. Procedures for applications mentioned are suggestions only and are not to be construed as representations or warranties as to performance, results, or fitness for any intended use, nor does PPG Industries Inc. warrant freedom from patent infringement in the use of any formula or process set forth herein.



PPG Industries
19699 Progress Drive
Strongsville, OH 44149
1-800-647-6050

PPG Canada Inc.
2301 Royal Windsor Drive Unit # 6
Mississauga, Ontario L5J 1K5
1-888-310-4762

Product Information effective 5/2026

The PPG Logo, Delflet, Delfleet Essential and OneChoice are registered trademarks and *Versolon* is a trademark of PPG Industries Ohio, Inc.
© 2026 PPG Industries, Inc. All rights reserved.