PROTECTION

TECHNICAL DATASHEET

MASKING TAPE PRECISION

PROGOLD

Product description



FSC
www.fsc.org
MIX
Paper
FSC® C170522

ProGold Masking Tape Precision is a premium masking tape designed for professional painters seeking precise and flawless paint results.

- Ideal for protecting skirting boards, door frames, sockets and switches during painting and renovation work.
- Its high-performance acrylic adhesive ensures reliable adhesion while preventing paint bleed, even with low-viscosity paints.
- The tape offers up to 60 days of clean indoor removal and up to 7 days outdoors.
- Its UV- and oxidation-resistant adhesive maintains consistent performance over time.
- Heat-resistant up to 120°C during short-term exposure.
- FSC™ certified, it is produced using paper sourced from responsibly managed forests.

Ideal to deliver exceptionally sharp paint lines and clean color separations.

Characteristics

Washi Paper
Acrylic Glue

Colour

Yellow

Sizes

18mm / 24mm / 36 mm / 48mm
X50M

Usage

The tape adheres perfectly to the surface; it does not bleed through. The tape is also ideal for protecting baseboards, door frames, outlets, and light switches - which have not been removed during renovation - from paint splatters.

Storage

The product should be stored in a cool and dry environment, avoiding sunlight, refrigeration and high temperature.
Shelf life is 12 months under normal temperature and humidity conditions. Working temperature -5°C to 30°C.

Technical information

Properties	Unit	Data range
Total Thickness	um	105 ±10
UV Resistant Days	Day	60 Int / 7 Ext