

DESCRIPTION

Johnstone's Trade UltraLast Matt is a premium quality scuff resilient, matt wall paint that is stain resistant and can be easily cleaned without polishing. The scuff resilience makes it long lasting and perfectly suited for high footfall areas, commercial environments, and public buildings. The low emission levels mean that UltraLast Matt has a reduced impact on indoor air quality.

RECOMMENDED USES

INTERIOR

Suitable for interior use on walls and ceilings.



TYPE OF SUBSTRATE

Suitable for interior use on previously coated walls & ceilings, as well as new or old dry plaster, dry lining (plaster boards) brick, block, concrete, cement render, primed metal & timber.

COLOUR RANGE

Available in a full colour palette via the Johnstone's Tinting System

FINISH

Matt.

VOLUME SOLID

43%

COVERAGE

COVERAGE

15
M²/LITRE

Johnstone's Trade UltraLast Matt will cover up to 15 square metres per litre depending on the nature and porosity of the surface being painted.

DRYING TIME

RECOAT

4
HRS

Touch dry in 1-2 hours. Recoatable after 4 hours.

TRANSPORTATION & STORAGE


To avoid the risk of spillage, always store and transport in a secure upright position. Do not use empty container for storing food. PROTECT FROM FROST.

THINNER

Thinner: Clean water.

VOC CONTENT

EU Limit Value for this product (Cat A/a): 30g/l (2010). This product contains max 1g/l VOC



KEY PROPERTIES

- Resilient Scuff Protection
- Stain resistant and easily cleaned
- Extends maintenance programmes
- Scrub Class 1

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. For more information and free Johnstone's Trade datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Do not breathe spray. Wear respiratory protection. Stir well before use and apply by brush, roller or spray. For best results on smooth surfaces a short pile roller is recommended. For best results on smooth and slight textured, a medium pile is recommended. For bare or porous surfaces add a mist coat, primer, or thinning ratios if required.

SPRAY APPLICATION

Airless spray application: undiluted, spray @ 2000-2500 PSI with 0.013"-0.017" tip.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

CLEANING STAINS

Apply all-purpose cleaner to sponge, or soft cloth and wipe away stain from the surface, rinse with clean water and dry.

SIZES

5 Litre & 10 Litre.