Jonmat Plus Contract Matt

DESCRIPTION

Johnstone's Trade Jonmat Plus is a high-quality, yet cost-effective anti-flash* contract matt emulsion, specifically formulated for new build projects. It delivers a permeable, breathable flat matt finish that can be spot repaired, helping maintain a consistent, uniform appearance.
Perfect for use on taped and jointed surfaces, as well as new plaster and dry lining board.

* Application in accordance with BS 6150:2019 and manufacturer's instructions

KEY PROPERTIES

- Developed specifically for new build construction
- Ideal for new plaster and dry lining board
- Enhanced application

RECOMMENDED USES



Internal finish for all types of new build interior walls and ceilings including new plaster, plasterboard, concrete, blockwork, brickwork, cement render, dry lining etc.
Also suitable for aged plaster.

COLOUR RANGE

Available in Brilliant White, Magnolia and L Base only.

Over 8,000 colours (light and mid tones) are available via the Johnstone's tinting system.

FINISH

Flat Matt Finish
(‹2 % Sheen Level)

VOLUME SOLID

22%

COVERAGE



Johnstone's Trade Jonmat Plus Contract Emulsion will cover up to 16 square metres per litre depending on the nature and porosity of the surface being painted.

FILM THICKNESS

WET: 84um DRY: 19um

DRYING TIME



Touch dry in 1-2 hours.
Recoatable if required after 2-4 hours, under normal conditions.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Lift with care. PROTECT FROM FROST.

THINNER

Thinner: Clean Water

VOC CONTENT

EU limit value for this product (CatA/a): 30g/l (2010)
This product contains max 12g/l VOC



PREPARATION

All surfaces to be painted should be clean, dry and free from all surface contaminants. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly. Wear a suitable face mask if dry sanding. Avoid the inhalation of dust. Any efflorescence/salt deposits should be completely removed by dry brushing only.
Seal bare plaster or absorbent surfaces such as dry lining, jointing compounds with an initial coat of Johnstone's Trade Jonmat Plus Contract Matt Emulsion thinned up to 20% with clean water and allow to fully dry. For more information and free Johnstone's Trade Datasheets call 01924 354354 or visit www.johnstonestrade.com.

APPLICATION



Ensure good ventilation during application and drying. Stir well. Easy to apply by brush or roller. Also suitable for application by spray. Do not breathe spray. Wear respiratory protection. If more than one of a colour is to be used in the same area intermix before use and spot repair only from the same batch.
Do not apply in temperatures below 10°C or in damp conditions.

SPRAY APPLICATION

Airless spray application: undiluted, spray @ 2000-2500 PSI with 0.013"-0.019" tip.

SPRAY THINNING APPLICATION
Thinning; sealing new bare surfaces; up to 2 part clean water to 10 parts paint.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings.
Do not empty product into drains or watercourses, including when cleaning painting tools. Do not use empty container for storing food.

PRECAUTIONS

- Keep out of reach of children
- Avoid contact with skin and eyes
- Do not ingest
- Do not breathe spray. Wear respiratory protection
- If medical advice is needed have container or label to hand
- Please refer to Product Label & Safety Data Sheet (SDS) for hazard warnings and information on safe handling/use/transport/storage/disposal/emergency
- SDS available : www.johnstonestrade.com or call 01924 354354

SIZES

5, 10 and 15 litre